



## **SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

---

### **SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

#### **1.1. Product identifier**

- Product name : GESSO SPRAY
- Product code : ODIF-GESSO.

#### **1.2. Relevant identified uses of the substance or mixture and uses advised against**

- White under layer.

#### **1.3. Details of the supplier of the safety data sheet**

- Registered company name: ODIF.
- Address : 118, chemin du Sermoraz - BP 413.01704.BEYNOST Cedex.France.
- Telephone : +33 (0)4 78 55 07 43. Fax : +33 (0)4 72 25 84 63.
- Email: [odif@odif.com](mailto:odif@odif.com)
- <http://www.odif.com>

#### **1.4. Emergency telephone number : +33 (0)1 45 42 59 59.**

- Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

---

### **SECTION 2 : HAZARDS IDENTIFICATION**

#### **2.1. Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

- Flammable aerosol, Category 1.

- Eye irritation, Category 2.
- Specific target organ toxicity (single exposure), Category 3.
- This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

**In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.**

- Extremely flammable.
- Vapors may cause drowsiness and dizziness.
- This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

**2.2. Label elements**

- Mixture for aerosol application.

**In compliance with EC regulation No. 1272/2008 and its amendments.**

- Hazard pictograms :



**GHS07      GHS02**

- Signal Word :
- DANGER
- Hazard statements :

H222	Extremely flammable aerosol.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

- Precautionary statements - General :

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

- Precautionary statements - Prevention :

P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

P280	Wear protective gloves/protective clothing/eye protection/face protection.
------	--

- Precautionary statements - Response :

P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/attention.

- Precautionary statements - Storage :

P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

- Precautionary statements - Disposal:

P501	Dispose of contents/container at a disposal facility in accordance with local regulations.
------	--

**In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.**

- Hazard symbols :



**Extremely flammable**

- Risk phrase :

R 12	Extremely flammable.
R 67	Vapours may cause drowsiness and dizziness.

- Safety phrase:

S 16	Keep away from sources of ignition - No smoking.
S 2	Keep out of the reach of children.
S 46	If swallowed, seek medical advice immediately and show this container or label.
Pressurized container: protect from sunlight and do not expose to	

temperatures exceeding 50°C.	
Do not pierce or burn, even after use.	
Do not spray on a naked flame or any incandescent material.	

### 2.3. Other hazards

- No data available.

## **SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1. Substances

- No substances fulfil the criteria set forth in annexe II section A of the REACH regulation (EC) n° 1907/2006.

### 3.2. Mixtures

#### Composition :

Identification	Name	Classification	%
INDEX: 603-019-00-8 CAS: 115-10-6 EC: 204-065-8	DIMETHYL ETHER	GHS02, GHS04, Dgr F+ H:220 R: 12	25 <= x % < 50
CAS: 67-64-1 EC: 200-662-2 REACH: 01-2119471330-49-0010	ACETONE	GHS07, GHS02, Dgr Xi,F H:225-319-336 EUH:066 R: 11-36-66-67	10 <= x % < 25
CAS: 64-17-5 EC: 200-578-6	ETHANOL	GHS02, Dgr F H:225 R: 11	10 <= x % < 25
CAS: 13463-67-7 EC: 236-675-5 REACH: 01-2119489379-17	TITANIUM DIOXIDE		2.5 <= x % < 10
CAS: 112926-00-8	SILICA, AMORPHOUS		1 <= x % < 2.5
CAS: 67-56-1 EC: 200-659-6 REACH: 01-2119433307-44	METHANOL	GHS06, GHS08, GHS02, Dgr T,F H:225-301-311-331-370 R: 11-23/24/25-39/23/24/25	0 <= x % < 1

## **SECTION 4 : FIRST AID MEASURES**

- As a general rule, in case of doubt or if symptoms persist, always call a doctor.
- NEVER induce swallowing by an unconscious person.

#### **4.1. Description of first aid measures**

##### **In the event of exposure by inhalation :**

- In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.
- If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.
- If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

##### **In the event of splashes or contact with eyes :**

- Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
- If there is any redness, pain or visual impairment, consult an ophthalmologist.

##### **In the event of swallowing :**

- In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.
- Keep the person exposed at rest. Do not force vomiting.
- Seek medical attention, showing the label.
- If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

#### **4.2. Most important symptoms and effects, both acute and delayed**

- No data available.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

- No data available.

---

## **SECTION 5 : FIREFIGHTING MEASURES**

- Flammable.
- Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

#### **5.1. Extinguishing media**

- Keep packages near the fire cool, to prevent pressurised containers from bursting.

##### **Suitable methods of extinction**

- In the event of a fire, use :
  - - sprayed water or water mist
  - - water with AFFF (Aqueous Film Forming Foam) additive
  - - halon
- Prevent the effluent of fire-fighting measures from entering drains or waterways.

### **Unsuitable methods of extinction**

- In the event of a fire, do not use :
- - water jet

### **5.2. Special hazards arising from the substance or mixture**

- A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.
- Do not breathe in smoke.
- In the event of a fire, the following may be formed :
- - carbon monoxide (CO)
- - carbon dioxide (CO<sub>2</sub>)

### **5.3. Advice for firefighters**

- Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

## **SECTION 6 : ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

- Consult the safety measures listed under headings 7 and 8.

#### **For non fire-fighters**

- Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.
- Avoid inhaling the vapors.
- Avoid any contact with the skin and eyes.
- If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

#### **For fire-fighters**

- Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

### **6.2. Environmental precautions**

- Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.
- Prevent any material from entering drains or waterways.

### **6.3. Methods and material for containment and cleaning up**

- Clean preferably with a detergent, do not use solvents.

### **6.4. Reference to other sections**

- No data available.

---

## **SECTION 7 : HANDLING AND STORAGE**

- Requirements relating to storage premises apply to all facilities where the mixture is handled.

### **7.1. Precautions for safe handling**

- Always wash hands after handling.
- Remove and wash contaminated clothing before re-using.
- Ensure that there is adequate ventilation, especially in confined areas.

#### **Fire prevention :**

- Handle in well-ventilated areas.
- Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.
- Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.
- Do not spray on a naked flame or any incandescent material.
- Do not pierce or burn, even after use.
- Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.
- Keep packages tightly closed and away from sources of heat, sparks and naked flames.
- Do not use tools which may produce sparks. Do not smoke.
- Prevent access by unauthorised personnel.

#### **Recommended equipment and procedures :**

- For personal protection, see section 8.
- Observe precautions stated on label and also industrial safety regulations.
- Do not breathe in aerosols.
- Avoid inhaling vapors.
- Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.
- Provide vapor extraction at the emission source and also general ventilation of the premises.
- Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.
- In all cases, recover emissions at source.
- Avoid eye contact with this mixture.
- Packages which have been opened must be reclosed carefully and stored in an upright position.

#### **Prohibited equipment and procedures :**

- No smoking, eating or drinking in areas where the mixture is used.

### **7.2. Conditions for safe storage, including any incompatibilities**

- No data available.

## Storage

- Keep out of reach of children.
- Keep the container tightly closed in a dry, well-ventilated place
- Keep away from all sources of ignition - do not smoke.
- Keep well away from all sources of ignition, heat and direct sunlight
- The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.
- Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

## Packaging

- Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

- No data available.

---

## **SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1. Control parameters

#### Occupational exposure limits :

- - European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
115-10-6	1920	1000	-	-	-
67-64-1	1210	500	-	-	-
67-56-1	260	200	-	-	Peau

- - ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
67-64-1	500 ppm	750 ppm	-	-	-
64-17-5	1000 ppm	-	-	-	-
13463-67-7	10 mg/m3	-	-	-	-
67-56-1	200 ppm	250 ppm	-	-	-

- - Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
115-10-6	1000 ml/m3	1900 mg/m3	8(II)	DFG
67-64-1	500 ml/m3	1200 mg/m3	2(I)	DFG



64-17-5	500 ml/m3	960 mg/m3	2(II)	DFG, Y
67-56-1	200 ml/m3	270 mg/m3	4(II)	DFG, EU, H, Y

- Belgium (Order of 19/05/2009, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
115-10-6	1000 ppm	-	-	-	-
67-64-1	500 ppm	1000 ppm	-	-	-
64-17-5	1000 ppm	-	-	-	-
13463-67-7	10 mg/m3	-	-	-	-
112926-00-8	10 mg/m3	-	-	-	-
67-56-1	200 ppm	250 ppm	-	-	-

- France (INRS - ED984:2007 and French Order of 30/06/2004) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
115-10-6	1000	1920	-	-	-	-
67-64-1	500	1210	1000	2420	-	84
64-17-5	1000	1900	5000	9500	-	84
13463-67-7	-	10	-	-	-	-
67-56-1	200	260	-	-	(12)	84

- Switzerland (SUVA 2009) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Temps :	RSB :
115-10-6	1910	1000	-	-	-	-
67-64-1	1200	500	2400	1000	4x15	B
64-17-5	960	500	1920	1000	4x15	-
13463-67-7	3a	-	-	-	-	-
67-56-1	260	200	1040	800	4x15	RB

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
115-10-6	400 ppm	500 ppm	-	-	-
67-64-1	500 ppm	1500 ppm	-	-	-
64-17-5	1000 ppm	-	-	-	-
13463-67-7	10 mg/m3	-	-	-	TI
67-56-1	200 ppm	250 ppm	-	-	-

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

- Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



- Use personal protective equipment that is clean and has been properly maintained.
- Store personal protective equipment in a clean place, away from the work area.
- Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

- Avoid contact with eyes.
- Use eye protectors designed to protect against liquid splashes
- Before handling, wear safety goggles with protective sides accordance with standard EN166.
- In the event of high danger, protect the face with a face shield.
- Prescription glasses are not considered as protection.
- Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.
- Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

- Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.
- Gloves must be selected according to the application and duration of use at the workstation.
- Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.
- Type of gloves recommended :
- - PVA (Polyvinyl alcohol)
- Recommended properties :
- - Impervious gloves in accordance with standard EN374

#### - Body protection

- Work clothing worn by personnel shall be laundered regularly.
- After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

- Avoid breathing vapours.
- If the ventilation is insufficient, wear appropriate breathing apparatus.
- When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.
- Type of FFP mask :

- Wear a disposable half-mask aerosol filter in accordance with standard EN149.
- Category :
- - FFP1
- Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :
- - A1 (Brown)
- Particle filter according to standard EN143 :
- - P1 (White)

---

## **SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

### **9.1. Information on basic physical and chemical properties**

#### **General information :**

Physical state:	fluid liquid.
spray.	
Colour:	White.

#### **Important health, safety and environmental information**

pH of the substance or preparation :	not relevant.
--------------------------------------	---------------

- The pH is impossible to measure or its value is not relevant.

Flash point interval :	not relevant.
Vapour pressure :	Below 110 kPa (1.10 bar).
Density :	< 1
Water solubility :	Insoluble.

#### **9.2. Other information**

- No data available.

---

## **SECTION 10 : STABILITY AND REACTIVITY**

### **10.1. Reactivity**

- No data available.

### **10.2. Chemical stability**

- This mixture is stable under the recommended handling and storage conditions in section 7.

### **10.3. Possibility of hazardous reactions**

- When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

### **10.4. Conditions to avoid**

- Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.
- Avoid :
- - heat

#### 10.5. Incompatible materials

- Keep away from :
- - oxidising agents

#### 10.6. Hazardous decomposition products

- The thermal decomposition may release/form :
- - carbon monoxide (CO)
- - carbon dioxide (CO<sub>2</sub>)

---

## **SECTION 11 : TOXICOLOGICAL INFORMATION**

### 11.1. Information on toxicological effects

- Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.
- Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.
- Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.
- May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.
- Splashes in the eyes may cause irritation and reversible damage
- Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.
- Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

#### Substances

##### Acute toxicity :

SILICA, AMORPHOUS (CAS: 112926-00-8)	
Oral route :	DL50 > 5000 mg/kg
	Species : Rat (recommended by the CLP)
Dermal route :	DL50 > 5000 mg/kg
	Species : Rabbit (recommended by the CLP)
ACETONE (CAS: 67-64-1)	
Oral route :	DL50 > 5000 mg/kg
	Species : Rat (recommended by the CLP)

Oral route :	DL50 = 5800 mg/kg
Dermal route :	DL50 > 5000 mg/kg
	Species : Rat (recommended by the CLP)
Dermal route :	DL50 = 20000 mg/kg
Inhalation route (Vapours) :	CL50 >= 20 mg/l
	Species : Rat (recommended by the CLP)
Inhalation route :	CL50 = 76 mg/l

### Mixture

- No toxicological data available for the mixture.

### Monograph(s) from the IARC (International Agency for Research on Cancer) :

- CAS 9003-20-7 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.
- CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.
- CAS 13463-67-7 : IARC Group 2B : The agent is possibly carcinogenic to humans.

---

## **SECTION 12 : ECOLOGICAL INFORMATION**

### 12.1. Toxicity Substances

- Substances classified as category 1 acute toxicity :

SILICA, AMORPHOUS (CAS: 112926-00-8)	
Fish toxicity :	Duration of exposure : 96 h
	CL50 > 10000 mg/l
	Species : Danio rerio
Crustacean toxicity :	Duration of exposure : 24 h
	CE50 = 1000 mg/l
	Species : Daphnia magna
ACETONE (CAS: 67-64-1)	
Fish toxicity :	Duration of exposure : 96 h
	CL50 > 100 mg/l
	CL50 = 5540 mg/l
Crustacean toxicity :	Duration of exposure : 48 h
	CE50 > 100 mg/l

	CE50 = 8800 mg/l
--	------------------

- Substances classified as category 1 chronic toxicity :

METHANOL (CAS: 67-56-1)	
Fish toxicity :	Duration of exposure : 96 h
	CL50 = 10800 mg/l
Crustacean toxicity :	Duration of exposure : 48 h
	CE50 = 24500 mg/l
Algae toxicity :	Duration of exposure : 72 h
	CEr50 = 8000 mg/l
ETHANOL (CAS: 64-17-5)	
Fish toxicity :	Duration of exposure : 96 h
	CL50 = 11400 mg/l
Algae toxicity :	Duration of exposure : 24 h
	CEr50 = 5000 mg/l

### Mixtures

- No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

- No data available.

### 12.3. Bioaccumulative potential

- No data available.

### 12.4. Mobility in soil

- No data available.

### 12.5. Results of PBT and vPvB assessment

- No data available.

### 12.6. Other adverse effects

- No data available.

**German regulations concerning the classification of hazards for water (WGK) :**

- WGK 1 (VwVwS vom 27/07/2005, KBws) : Slightly hazardous for water.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

- Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

- Do not pour into drains or waterways.

**Waste :**

- Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.
- Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.
- Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

- Empty container completely. Keep label(s) on container.
- Give to a certified disposal contractor.

---

**SECTION 14 : TRANSPORT INFORMATION**

- Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2011 - IMDG 2010 - ICAO/IATA 2011).

**14.1. UN number**

- 1950

**14.2. UN proper shipping name**

- UN1950=AEROSOLS, flammable

**14.3. Transport hazard class(es)**

- - Classification :



- 2.1

#### 14.4. Packing group

- -

#### 14.5. Environmental hazards

- -

#### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D	
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
2.1	SP63	-	SP277	F-D,S-U	63 190 277 327 959	E0				
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
2.1	-	-	203	75 kg	203	150 kg	A145 A167	E0		
2.1	-	-	Y203	30 kg G	-	-	A145 A167	E0		

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

- No data available.

## **SECTION 15 : REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture - Particular provisions :

- No data available.

#### - German regulations concerning the classification of hazards for water (WGK):

- Germany: WGK 1 (VwVwS vom 27/07/2005, KBws)

#### 15.2. Chemical safety assessment

- No data available.



---

## **SECTION 16 : OTHER INFORMATION**

- Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.
- The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.
- It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.
- The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### **Title for H, EUH and R indications mentioned in section 3 :**

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs .
EUH066	Repeated exposure may cause skin dryness or cracking.
R 11	Highly flammable.
R 12	Extremely flammable.
R 23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R 36	Irritating to eyes.
R 39/23/24/25	Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
R 66	Repeated exposure may cause skin dryness or cracking.
R 67	Vapours may cause drowsiness and dizziness.

### **Abbreviations :**

- ADR : European agreement concerning the international carriage of dangerous goods by Road.
- IMDG : International Maritime Dangerous Goods.
- IATA : International Air Transport Association.
- ICAO : International Civil Aviation Organisation
- RID : Regulations concerning the International carriage of Dangerous goods by rail.
- WGK : Wassergefahrdungsklasse (Water Hazard Class).