



## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : COLLE THERMOFIXABLE / COLLAGE THERMOCOLLANT  
Product code : ODIF-606.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Spray adhesive.

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : ODIF.  
Address : 118, chemin du Sermoraz - BP 413.01704.BEYNOST Cedex.France.  
Telephone : +33 (0)4 78 55 07 43. Fax : +33 (0)4 72 25 84 63.  
Email: odif@odif.com  
<http://www.odif.com>

#### 1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

#### 2.2. Label elements

Mixture for aerosol application.

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02

Signal Word :

DANGER

Hazard statements :

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.

Precautionary statements - Storage :

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 115-10-6 EC: 204-065-8 REACH: 01-2119472128-37  DIMETHYL ETHER	GHS02 Dgr Flam. Gas 1, H220	[1]	50 $\leq$ x % < 65.2
CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32  BUTANE	GHS04, GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280	C [1]	10 $\leq$ x % < 28.6
CAS: 74-98-6 EC: 200-827-9 REACH: 01-2119486944-21  PROPANE	GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	2.5 $\leq$ x % < 6.2

(Full text of H-phrases: see section 16)

Information on ingredients :

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

In the event of exposure by inhalation :

If inhaled, move the patient into the fresh air and keep warm and at rest.

If breathing is irregular or has stopped, proceed with artificial respiration and seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist

- water with AFFF (Aqueous Film Forming Foam) additive
  - halon
  - multipurpose ABC powder
  - BC powder
- Prevent the effluent of fire-fighting measures from entering drains or waterways.

#### Unsuitable methods of extinction

- In the event of a fire, do not use :
- water jet

#### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

#### 5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Ensure that there is adequate ventilation, especially in confined areas.

#### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Packages which have been opened must be reclosed carefully and stored in an upright position.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

### Packaging

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Occupational exposure limits :

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m <sup>3</sup> :	VME-ppm :	VLE-mg/m <sup>3</sup> :	VLE-ppm :	Notes :
115-10-6	1920	1000	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm				
74-98-6	1000 ppm				

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
115-10-6		1000 ppm 1900 mg/m <sup>3</sup>		8(II)
106-97-8		1000 ppm 2400 mg/m <sup>3</sup>		4(II)
74-98-6		1000 ppm 1800 mg/m <sup>3</sup>		4(II)

- Belgium (Arrêté du 09/03/2014, 2014) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
115-10-6	1000 ppm 1920 mg/m <sup>3</sup>				
106-97-8	1000 ppm				
74-98-6	1000 ppm				

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
115-10-6	1000	1920	-	-	-	-
106-97-8	800	1900	-	-	-	-

- Switzerland (SUVA PRO 2017) :

CAS	VME	VLE	Valeur plafond	Notations
115-10-6	1000 ppm 1910 mg/m <sup>3</sup>			
106-97-8	800 ppm 1900 mg/m <sup>3</sup>	3200 ppm 7200 mg/m <sup>3</sup>		
74-98-6	1000 ppm 1800 mg/m <sup>3</sup>	4000 ppm 7200 mg/m <sup>3</sup>		

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
115-10-6	400 ppm 766 mg/m <sup>3</sup>	500 ppm 958 mg/m <sup>3</sup>			
106-97-8	600 ppm 1450 mg/m <sup>3</sup>	750 ppm 1810 mg/m <sup>3</sup>		Carc	

- USA / AIHA WEEL (American Industrial Hygiene Association, Workplace Environmental Exposure Limit, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
115-10-6	1000 ppm				

#### Derived no effect level (DNEL) or derived minimum effect level (DMEL):

DIMETHYL ETHER (CAS: 115-10-6)

**Final use:**

Exposure method:  
Potential health effects:  
DNEL :

**Workers.**

Inhalation.  
Long term systemic effects.  
1894 mg of substance/m3

Exposure method:  
Potential health effects:  
DNEL :

Inhalation.  
Short term systemic effects.  
471 mg of substance/m3

**Predicted no effect concentration (PNEC):**

DIMETHYL ETHER (CAS: 115-10-6)

Environmental compartment: Soil.  
PNEC : 0.045 mg/kg

Environmental compartment: Fresh water.  
PNEC : 0.155 mg/l

Environmental compartment: Sea water.  
PNEC : 0.016 mg/l

Environmental compartment: Fresh water sediment.  
PNEC : 0.681 mg/kg

Environmental compartment: Marine sediment.  
PNEC : 0.069 mg/kg

Environmental compartment: Waste water treatment plant.  
PNEC : 180 mg/l

**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

**- Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

**- Body protection**

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties****General information :**

Physical state :	Fluid liquid.
	Spray.

**Important health, safety and environmental information**

pH :	Not relevant.
Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).

Density :	< 1
Water solubility :	Insoluble.
Chemical combustion heat :	Not specified.
Inflammation time :	Not specified.
Deflagration density :	Not specified.
Inflammation distance :	Not specified.
Flame height :	Not specified.
Flame duration :	Not specified.

**9.2. Other information**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

**10.5. Incompatible materials**

Keep away from :

- strong acids
- strong oxidising agents

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

Splashes in the eyes may cause irritation and reversible damage

**11.1.1. Substances****Acute toxicity :**

BUTANE (CAS: 106-97-8)

Inhalation route (n/a) :

LC50 = 658 mg/l

Species : Rat

Duration of exposure : 4 h

DIMETHYL ETHER (CAS: 115-10-6)

Inhalation route (n/a) :

LC50 = 312 mg/l

Species : Rat

Duration of exposure : 4 h

**11.1.2. Mixture**

No toxicological data available for the mixture.

**SECTION 12 : ECOLOGICAL INFORMATION****12.1. Toxicity****12.1.1. Substances**

BUTANE (CAS: 106-97-8)

Fish toxicity :

LC50 = 24.11 mg/l

Duration of exposure : 96 h

Crustacean toxicity :  
EC50 = 14.22 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

DIMETHYL ETHER (CAS: 115-10-6)  
Fish toxicity :  
LC50 > 4000 mg/l  
Species : Poecilia reticulata  
Duration of exposure : 96 h

Crustacean toxicity :  
EC50 > 4000 mg/l  
Species : Daphnia magna  
Duration of exposure : 48 h

### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

## 12.2. Persistence and degradability

### 12.2.1. Substances

BUTANE (CAS: 106-97-8)  
Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

DIMETHYL ETHER (CAS: 115-10-6)  
Biodegradability : Non-rapidly degradable.

## 12.3. Bioaccumulative potential

### 12.3.1. Substances

BUTANE (CAS: 106-97-8)  
Octanol/water partition coefficient : log K<sub>ow</sub> < 3.

DIMETHYL ETHER (CAS: 115-10-6)  
Octanol/water partition coefficient : log K<sub>ow</sub> = 0.18

Bioaccumulation : BCF < 100.

## 12.4. Mobility in soil

No data available.

## 12.5. Results of PBT and vPvB assessment

No data available.

## 12.6. Other adverse effects

No data available.

## German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 1 : Slightly hazardous for water.

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

## SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2019).

**14.1. UN number**

1950

**14.2. UN proper shipping name**

UN1950=AEROSOLS, flammable

**14.3. Transport hazard class(es)**

- Classification :



2.1

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	2	See SP63	-	See SP277	F-D, S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	2.1	-	Forbidden	Forbidden	203	150 kg	A1 A145 A167 A802	E0	
	2.1	2.1	-	Forbidden	Forbidden	-	-	A1 A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**SECTION 15 : REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2019/521 (ATP 12)

**- Container information:**

No data available.

**- Particular provisions :**

No data available.


**- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :**

WGK 1 : Slightly hazardous for water.

**- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :**

NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



**- Swiss ordinance on the incentive tax on volatile organic compounds :**

115-10-6	éther diméthylique (oxyde de diméthyle)
75-28-5	2-méthylpropane (alcool isobutylique, isobutane)
106-97-8	n-butane
74-98-6	propane

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.